

The SL16 Multibolt has gained an enviable reputation in all markets for strength and reliability in over 17 years of successful service.

Performing to in excess of 9Kn during PAS24 testing, SL16 is one of the most secure locks available and is widely used on PVCu, Composite, Timber, Steel and Aluminium doors.

PAS23 and PAS24 tested

Tapered long throw top and bottom deadbolts offer high security and compression

Handles available with latch hold back snib

Split spindle option for use on front door applications

Easily reversible latch as standard

304 grade stainless steel faceplate for high corrosion resistance



Technical Data

Corrosion Resistance

BSEN1670 Grade 5 (480 hours)

Cyclic Operation

Cycles Tested to 100,000 cycles

Materials

Top and Bottom Hooks

CZ122 brass stamping

Deadbolt

CZ122 brass stamping

Centre Deadbolt

CZ122 brass stamping

Faceplate

304 austenitic stainless steel

Gearbox

Dacromet coated die cast zinc

For maximum security the SL16 lock can be used with the Kinetica 3 star BSI Kitemarked TS007 cylinder.



The SL16 deadbolts are chamfered to pull in smoothly and have a 25mm long throw for maximum security on any door type.

The 2 + 2 lock was the FIRST lock manufactured in the UK to offer the now very popular hook and bolt combination.

The SL16 lock forms the basis for two further very successful Fullex products, the Gemini interlocking double door system and the Pyroscape panic exit lock.

Faceplate = 1770mm x 20mm (Stainless Steel):

Product Code	Spindle	Backset Size	Faceplate Width	Latch Size	Handle Backplate	Handle Centres	No of Hooks	Hook Direction	No of Deadbolts	No of Anti-Lift Bolts
SL160053	Split	35mm	20mm	51mm	240mm	68PZ	0	-	3	0
SL160054	Split	35mm	20mm	51mm	240mm	68PZ	1	Down	3	0
SL160108	Split	45mm	20mm	51mm	240mm	68PZ	0	-	3	0
SL160107	Split	45mm	20mm	51mm	240mm	68PZ	1	Down	3	0
SL160074	Split	55mm	20mm	51mm	240mm	68PZ	0	-	3	0
SL160049	Split	55mm	20mm	51mm	240mm	68PZ	1	Down	3	0

Faceplate = 2200mm (Stainless Steel):

Product Code	Spindle	Backset Size	Faceplate Width	Latch Size	Handle Backplate	Handle Centres	No of Hooks	Hook Direction	No of Deadbolts	No of Anti-Lift Bolts
SL160004	Split	35mm	16mm	51mm	240mm	68PZ	0	-	3	0
SL160018	Split	35mm	16mm	51mm	240mm	68PZ	1	Down	3	0
SL160073	Split	35mm	20mm	51mm	240mm	68PZ	0	-	3	0
SL160128	Split	45mm	20mm	51mm	240mm	68PZ	0	-	3	0
SL160039	Split	35mm	22mm	51mm	240mm	68PZ	0	-	3	0

Faceplate = 2150mm (Stainless Steel):

Used on the Fullex Gemini system

Product Code	Spindle	Backset Size	Faceplate Width	Latch Size	Handle Backplate	Handle Centres	No of Hooks	Hook Direction	No of Deadbolts	No of Anti-Lift Bolts
SL160139	Split	45mm	25mm	51mm	240mm	68PZ	0	-	3	0

