

## Technical data sheet

**SIMPSON**

**Strong-Tie**

POLY-GP

### General Purpose Resin Mortar

Chemical anchor for use in concrete and masonry. Specially formulated for light or medium duty fixing into hollow or solid base materials. Poly-GP300 is easy to use and fast curing, it enables good performance when used in applications such as fixing architectural steel work, cable trays, hand rails and gates.

## Features

### Material

- Styrene free polyester
- Use with Simpson Strong-Tie threaded rod (LMAS) : galvanised steel and stainless A4-70

### Benefits

- Fast curing.
- Non-flammable.
- Low odour.
- Colour changes when cured.


## Applications

### Header member

**Hollow or solid masonry.**

### For Use With

- Blinds
- Hinges
- Air conditioners
- Satellite Dishes
- Boilers



Fixation d'une cloture



## Technical data sheet

**SIMPSON****Strong-Tie**

POLY-GP

**General Purpose Resin Mortar**

## Technical Data

### Item Codes

References	Color	Content [ml]	Weight [kg]
POLY-GP380-FR*	Beige	380	0.9
Poly GP + LMAS M8*	-	-	-
Poly GP + LMAS M10*	-	-	-
Poly GP + LMAS M12*	-	-	-

Two nozzles are supplied with each cartridge. Downloadable Safety Data Sheet available from [www.strongtie.eu](http://www.strongtie.eu)

### Performance Values

References	Tension [Rds,N] [kN]				Shear [Rds,V] [kN]			
	Solid Brick	Autoclaved aerated concrete blocks	Hollow Brick	Hollow concrete block	Solid Brick	Autoclaved aerated concrete blocks	Hollow Brick	Hollow concrete block
Poly GP + LMAS M8*	0.72	0.26	0.43	0.26	0.72	0.26	0.43	0.26
POLY-GP380-FR*	-	-	-	-	-	-	-	-
Poly GP + LMAS M10*	0.72	0.35	0.43	0.35	0.72	0.35	0.43	0.35
Poly GP + LMAS M12*	0.72	0.35	0.57	0.35	0.72	0.35	0.57	0.35

Performance values are calculated from published data characteristic values in the ETA on which partial safety factors from ETA and a partial coefficient = 1.4 γf actions are applied. Service charges include the sealing position in the holder and is adhered to the method of installation. For hollow brackets unknown resistance, site of trials are needed (in accordance with ICASA recommendations for use by construction professionals for the construction of ankles tests on site).

## POLY-GP General Purpose Resin Mortar


## Installation

### Curing Schedule

Temp of Support	-5°C	0°C	5°C	10°C	15°C	20°C	30°C
Working Time	25min	15min	12min	8min	7min	4min	2min
Curing Time	4h	3h	2h30	1h15	55min	30min	20min



Drill.




Brush.



Insert sieve.



Inject the resin.




Insert the rod, turning slowly.



Once set, full load capacity is reached.



Drill.



Remove dust by brushing and blowing.



Fill the hole to half or two thirds. Withdrawing the nozzles with each pump.



Insert the rod, turning slowly.



Once set, full load capacity is reached.

### Solid Brick Installation



References	Ø drilling diameter [d0] [mm]	Maximum diameter of hole in the fixture [df] [mm]	Depth of the drilling hole [h1] [mm]	Wrench Size [Sw]	Installation Torque [Tinst] [Nm]	Depth of the drilling hole [hef] [mm]	Characteristic spacing - S <sub>Cr,N</sub> [mm]	Minimum spacing - S <sub>min</sub> [mm]	Characteristic edge distance - C <sub>Cr,N</sub> [mm]	Minimum edge distance - C <sub>min</sub> [mm]
Poly GP + LMAS M8*	10	9	85	13	4	80	160	50	80	50
POLY-GP380-FR*	-	-	-	-	-	-	-	-	-	-
Poly GP + LMAS M10*	12	12	85	15	6	80	200	50	100	50
Poly GP + LMAS M12*	14	14	85	18	8	80	240	50	120	50

# Technical data sheet

**SIMPSON**

**Strong-Tie**

POLY-GP

**General Purpose Resin Mortar**

Cellular Concrete



References	Ø drilling diameter [d0] [mm]	Maximum diameter of hole in the fixture [df] [mm]	Depth of the drilling hole [h1] [mm]	Wrench Size [Sw]	Installation Torque [Tinst] [Nm]	Depth of the drilling hole [hef] [mm]	Characteristic spacing - S <sub>cr,N</sub> [Nm]	Minimum spacing - S <sub>min</sub> [mm]	Characteristic edge distance - C <sub>cr,N</sub> [mm]	Minimum edge distance - C <sub>min</sub> [mm]
Poly GP + LMAS M8*	10	9	85	13	2	80	160	50	80	50
POLY-GP380-FR*	-	-	-	-	-	-	-	-	-	-
Poly GP + LMAS M10*	12	12	85	15	3	80	200	50	100	50
Poly GP + LMAS M12*	14	14	85	18	5	80	240	50	120	50

Foundation Brick



References	Ø drilling diameter [d0] [mm]	Size of the Sieve	Maximum diameter of hole in the fixture [df] [mm]	Depth of the drilling hole [h1] [mm]	Wrench Size [Sw]	Installation Torque [Tinst] [Nm]	Depth of the drilling hole [hef] [mm]	Characteristic spacing - S <sub>cr,N</sub> [mm]	Minimum spacing - S <sub>min</sub> [mm]	Characteristic edge distance - C <sub>cr,N</sub> [mm]	Minimum edge distance - C <sub>min</sub> [mm]
Poly GP + LMAS M8*	16	16x85 ou 16x130	9	135	13	4	130	500	100	250	100
POLY-GP380-FR*	-	-	-	-	-	-	-	-	-	-	-
Poly GP + LMAS M10*	16	16x85 ou 16x130	12	135	15	6	130	500	100	250	100
Poly GP + LMAS M12*	16	16x85 ou 16x130	14	135	18	6	130	500	100	250	100

Hollow Cinderblock



References	Ø drilling diameter [d0] [mm]	Size of the Sieve	Maximum diameter of hole in the fixture [df] [mm]	Depth of the drilling hole [h1] [mm]	Wrench Size [Sw]	Installation Torque [Tinst] [Nm]	Depth of the drilling hole [hef] [mm]	Characteristic spacing - S <sub>cr,N</sub> [mm]	Minimum spacing - S <sub>min</sub> [mm]	Characteristic edge distance - C <sub>cr,N</sub> [mm]	Minimum edge distance - C <sub>min</sub> [mm]
Poly GP + LMAS M8*	16	16x130	9	135	13	4	130	500	100	250	100
POLY-GP380-FR*	-	-	-	-	-	-	-	-	-	-	-
Poly GP + LMAS M10*	16	16x130	12	135	15	6	130	500	100	250	100
Poly GP + LMAS M12*	16	16x130	14	135	18	6	130	500	100	250	100

Winchester Road Cardinal Point Tamworth Staffordshire B78  
3HG  
tel: +44 1827 255600  
fax: +44 1827 255616

Copyright by Simpson Strong-Tie®

Information presented on this document is the exclusive property of Simpson Strong-Tie®  
It is valid only when associated with products supplied by Simpson Strong-Tie®

POLY-GP  
**General Purpose Resin  
Mortar**



[www.strongtie.co.uk](http://www.strongtie.co.uk)

**SIMPSON**  
**Strong-Tie**

2024-03-02