

XL is available in a range of lock configurations and can be used with either one piece or individual keep sets. The XL's attractive silver finish is also corrosion resistant to neutral salt spray in excess of BSEN1670 Grade 4, giving peace of mind to hard pressed fabricators and consumers.

Various 3 hook XL lock centres are available, with either 2 or 4 roller compression cams.

Other locks available include XLSL slave lock, XL4R centre hook, latch and 4 roller or XL2R2M centre hook, latch, 2 rollers and 2 mushroom cams.

PAS2424 tested

One piece or individual keeps

Three opposing steel hooks and two steel anti lift bolts

Two or four roller cams

Easily reversible latch as standard

Dual, single or split spindle options

Extendable top and bottom as standard

Latch hold back snib on lock faceplate

For use on PVCu doors



## Technical Data

### Corrosion Resistance

BSEN1670 Grade 4 (240 hours)

### Cyclic Operation

Cycles Tested to 200,000 cycles

## Materials

### Top and Bottom Hook

Chrome plated A3 hardened cast steel

### Anti Lift Bolts

Chrome plated A3 hardened cast steel

### Centre Hook

Dacromet coated A3 sintered steel

### Faceplate and Gearbox

Mild steel, zinc and clear passivated

### Roller Cams

Mild steel, zinc and clear passivated

For maximum security the XL Lock can be used with the Kinetica 3 star BSI Kitemarked TS007 cylinder.

