



Granville Hypalube FD FS 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

Product Description

Granville Hypalube FD 5W/30 is a fully synthetic engine oil designed to provide maximum protection for modern engines requiring a low viscosity oil. It is suitable for lean burn, multi-valve, injection, twin cam, turbo charged and Ford engines where this grade and specification of oil is required.

Recommended for use by Granville for the following manufacturer's specifications

Ford: WSS-M2C913-A, WSS-M2C913-B, WSS-M2C913-C & WSS-M2C913-D

ACEA: A5/B5

API: SL/CF

STJLR: .03.5003



* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	0047	5020618000471
5 Litre	0198	5020618001980
20 Litre	0412	5020618004127
199 Litre	0017	5020618000174

Product Benefits

- * Ensures lubricant performance over extended drain intervals
- * Excellent high and low temperature performance
- * Outstanding fuel efficiency
- * Effective environmental protection

Product Usage

For engines where this specification lubricant is required.

Directions for Use

As recommended by the engine manufacturer.

Storage Instructions

Keep sealed in a cool, dry place.

Shelf Life

5 years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water





Granville Hypalube FD FS 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

Test	Method	Unit	Min.	Max.	Typical
Kinematic Viscosity at 100°C	ASTM D445	mm ² /s	9.3	<12.5	10.42
Cold Cranking Viscosity	ASTM D4684	mPa.s		6600	
Pour Point	ASTM D97	°c		-27	
NOACK Volatility	ASTM D5800	%		13	
Total Base Number	ASTM D2896	mg KOH/g	10		11.48
Kinematic Viscosity at 40°C	ASTM D445	mm ² /s			57.63
Density	ASTM D792	@ 15°C			0.855
Viscosity Index	ASTM D2270				172.042

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

